



CASSETTE TYPE



WORLD STANDARD AIR CONDITIONERS

SUPER FLOW



*เย็นเร็วทันใจ
กระจายลมทั่วทิศทาง*

SPECIFICATIONS
CASSETTE TYPE
FIXED SPEED



SUPERFLOW

MODEL			Fancoil unit	CFG18F	CFG24F	CFG30F	CFG36F	CFG36F	CFG40F
			Condensing unit	AFE18FC	AFE24FC	AFE30FC	AFE36FC	AFE36FTC	AFE40FC
Cooling capacity		TIS. Watt		5,500	7,100	8,800	10,600	10,600	11,800
		EGAT. Btu/hr		19,000	25,000	31,000	36,100	36,100	40,944
Current		Amp		7.2	9.1	11.8	14.2	4.8	15.9
Power		TIS. Watt		1,510	1,950	2,500	3,010	3,010	3,360
COP		TIS. Watt/Watt		3.57	3.60	3.44	3.44	3.45	3.44
SEER		EGAT. (Btu/Hr)/Watt		13.70	13.70	13.50	13.12	13.50	13.12
Label No.5 Ranking				5	5	5★	5	5★	5
INDOOR UNIT	Power supply		V/Ph/Hz	220/1/50					
	Blower		Q'ty	1					
	Fan motor		Q'ty	1					
	Fan motor		Type	AC		DC			
	Air Direction			4 Ways , Auto Swing			8 Ways(Round Flow) , Auto Swing		
	Dimension	Front panel-WxDxH	m.m.	647x647x50		950x950x60			
		Body-Width	m.m.	570		840			
		Body-Depth	m.m.	570		840			
		Body-Height	m.m.	260		240	290		
	Net Weight(Front panel)		Kgs.	5		7			
Net Weight(Body)		Kgs.	22		29	33	33	34	
CONNECTION	Liquid		Inch	1/4		3/8			
	Suction		Inch	1/2		5/8			
	Drain		Inch	1					
Refrigerant Type				R32					
Flow control (Installed)				Capillary tube (ODU)					
OUTDOOR UNIT	Power supply		V/Ph/Hz	220/1/50			220/1/50	380/3/50	220/1/50
	Fan blade		Q'ty	1					
	Fan motor		Q'ty	1					
	Fan motor		Type	AC					
	Compressor		Type	Rotary			Scroll		
	Dimension	Width	m.m.	866	968				
		Depth	m.m.	308			356		
		Height	m.m.	641	794				
Net Weight		Kgs.	46	62	71	71	71	75	

MODEL			Fancoil unit	CFG40F	CFG44F	CFG48F	CFG54F	CFG60F	
			Condensing unit	AFE40FTC	AFE44FTC	AFE48FTC	AFE54FTC	AFE60FTC	
Cooling capacity		TIS. Watt		12,000	13,000	14,100	15,900	17,600	
		EGAT. Btu/hr		40,944	44,400	48,200	54,300	61,416	
Current		Amp		5.4	7.6	8.2	8.7	10.3	
Power		TIS. Watt		3,410	4,300	4,540	5,120	5,680	
COP		TIS. Watt/Watt		3.45	3.00	3.00	3.00	3.00	
SEER		EGAT. (Btu/Hr)/Watt		13.50	11.80	11.20	11.20	10.59	
Label No.5 Ranking				5★	5★★★	5★★	5★★	5	
INDOOR UNIT	Power supply		V/Ph/Hz	220/1/50					
	Blower		Q'ty	1					
	Fan motor		Q'ty	1					
	Fan motor		Type	DC					
	Air Direction			8 Ways(Round Flow) , Auto Swing					
	Dimension	Front panel-WxDxH		m.m.	950x950x60				
		Body-Width		m.m.	840				
		Body-Depth		m.m.	840				
		Body-Height		m.m.	290				
	Net Weight(Front panel)			Kgs.	7				
Net Weight(Body)			Kgs.	34	34	34	34	34	
CONNECTION	Liquid		Inch	3/8			1/2	1/2	
	Suction		Inch	5/8			3/4	3/4	
	Drain		Inch	1					
Refrigerant Type				R32					
Flow control (Installed)				Capillary tube (ODU)			Capillary tube (IDU)		
OUTDOOR UNIT	Power supply		V/Ph/Hz	380/3/50	380/3/50				
	Fan blade		Q'ty	1	2				
	Fan motor		Q'ty	1	2				
	Fan motor		Type	AC					
	Compressor		Type	Scroll					
	Dimension	Width		m.m.	968				
		Depth		m.m.	356				
		Height		m.m.	794	1151			
Net Weight			Kgs.	75	82	82	82	87	



WORLD STANDARD AIR CONDITIONERS



SIMILAR CO., LTD. (HEAD OFFICE)
235 Lasalle Road, Bangna-tai Sub-district,
Bangna District, Bangkok 10260 Thailand.

✉: marketing@eminent.co.th

🌐: www.eminent.co.th

📺: Eminent Air

☎: +66 2 083 5555

📞: +66 2 033 6235



Call Center ☎: +66 2 033 6229

📞: @eminentairservice

Distributed by

*29 February 2024